



Pressure, Level & Temperature Transmitters & Transducers

2770 Long Road, Grand Island, NY 14072 USA

Tel. (716) 773-9300 • Fax (716) 773-5019

sales@gp50.com • www.gp50.com

QUICK SHIP



GP:50's program for fast, efficient delivery of Industrial Test and Control Products. (Shipment in 2 days ARO)

Models 211 (0-5 Vdc) and 311 (4-20 mA) are available with all standard pressure ranges. Add any of the options below and you have a unit that will fit just about any application!

ORDERING:

Take a look below at our Easy To-Use Ordering Guide to select model number, Accuracy, Pressure Range, Pressure Type & the options that you need for your application, and expect shipment within 2 days ARO at no additional charge.

MODEL	SERIES	RANGE	PRESSURE TYPE	OPTIONS
311	C	PT	2	CA/GJ

Approvals



MODEL:

211 0-5 Vdc

311 4-20 mA

ACCURACY:

B 0.5% FSO

C 0.2% FSO

PRESSURE RANGE (PSI):

PJ 5	PX 75	RM 1,000
PL 7.5	PZ 100	RO 1,500
PN 10	RB 150	RR 2,000
PP 15	RD 200	RS 2,500
PQ 3-15	RE 250	RT 3,000
PR 20	RF 300	RV 5,000
PS 3-27	RH 500	RX 7,500
PO 25	RJ 600	RZ 10,000
PT 30	RK 750	SZ 0-5 to 0-10,000
PV 50		Non-Standard Range

PRESSURE TYPE:

- 2 Gauge (0-299 psi)
- 4 Vacuum
- 7 Gauge (Non-Hermetic Seal / 300 psi & above)
- 8 Elevated
- 10 Compound (vacuum to gauge)

OPTIONS:

- AA No Options chosen (1/4" NPT (F) pressure port & HEYCO w/36" wire lead electrical connection)
- CA Bendix 6-Pin conn. (PTIH-10-6P), or equivalent (Mate: not inc.)
- CF 1/2" NPT (M) thread with 36" potted leads
- CH NEMA-4X Rating with 8' vented cable (299 psi & below)
- CJ DIN 43650 (Hirshmann, w/mate) NEMA-4X (IP65)
- CL 1/2" NPT (M) with 36" vented cable (299 psi & below)
- CO Terminal block w/Junction box
- GJ Add Zero & Span Controls (Approx. ±20% FSO Adjustment)
- HK NEMA-4X Rating w/36" wire lead (300 psi & above)

A5SL-QS11.00 Rev A