



**MELT PRESSURE
TRANSDUCERS & TRANSMITTERS**

300 Industrial Drive, Grand Island, NY 14072 USA
Tel. (716)775-8830 • Fax (716)775-8020 • sales@gp50.com • www.gp50.com

Product Specification Sheet



QUICK SHIP

GP:50's program for fast, efficient delivery of **Melt Pressure Products**.
(Shipment in 3-5 days ARO)



ORDERING:

See the ordering guide below for the Models 30, 31 and 35 series of Melt Pressure Transducers.

Pick from the options below and receive a quick turnaround at **No Additional Charge**, just the standard shipping charge.

Must be labeled "Quick Ship" on purchase order or standard delivery will apply.

Model 130, 230, 330 - 6" Rigid Stem
Model 131, 231, 331 - 6" Rigid Stem 18" Flex
Model 135, 235, 335 - 6" Rigid Stem 18" Flex with Removable J Type Thermocouple

EXAMPLE:

MODEL	RANGE	OPTIONS
331	RX	CF/GJ

MODEL

130/131 3.33 mV/V
230/231 0-5Vdc
330/331 4-20 mA

135 3.33 mV/V
235 0-5Vdc
335 4-20mA

PRESSURE RANGE

RO 1,500 psi
RT 3,000 psi
RV 5,000 psi
RX 7,500 psi
RZ 10,000 psi

CONNECTOR OPTIONS

PTIH-10-6P Standard Connector
CC Bendix PC02E-12-8P
CD Cannon WK6-32S
CF 1/2" NPT (M) thread with 36" potted leads

GENERAL OPTIONS

GJ Model 1XX only
(Standard on 2XX and 3XX)
GS 0-10 Vdc Model 2XX only
GU Type K thermocouple (x35 only)

Wire termination to meet customer's requirements.