



**MELT PRESSURE
TRANSDUCERS & TRANSMITTERS**
2770 Long Road, Grand Island, NY 14072 USA
Tel. (716)773-9300 • Fax (716)773-5019 • sales@gp50.com • www.gp50.com

Product Specification Sheet



QUICK SHIP

GP:50's program for fast, efficient delivery of **Melt Pressure Products**.
(Shipment in 3-5 days ARO)



Model 130, 230, 330 - 6" Rigid Stem
Model 131, 231, 331 - 6" Rigid Stem 18" Flex
Model 135, 235, 335 - 6" Rigid Stem 18" Flex
with Removable J Type Thermocouple

MODEL	
130/131	3.33 mV/V
230/231	0-5Vdc
330/331	4-20 mA
135	3.33 mV/V
235	0-5Vdc
335	4-20mA

PRESSURE RANGE	
RO	1,500 psi
RT	3,000 psi
RV	5,000 psi
RX	7,500 psi
RZ	10,000 psi

ORDERING:

See the ordering guide below for the Models 30, 31 and 35 series of Melt Pressure Transducers.

Pick from the options below and receive a quick turnaround at **No Additional Charge**, just the standard shipping charge.

Must be labeled "Quick Ship" on purchase order or standard delivery will apply.

EXAMPLE:

MODEL	RANGE	OPTIONS
331	RX	CF/GJ

CONNECTOR OPTIONS

PTIH-10-6P	Standard Connector
CC	Bendix PC02E-12-8P
CD	Cannon WK6-32S
CF	1/2" NPT (M) thread with 36" potted leads

GENERAL OPTIONS

GJ	Model 1XX only (Standard on 2XX and 3XX)
GS	0-10 Vdc Model 2XX only
GU	Type K thermocouple (x35 only)

Wire termination to meet customer's requirements.