



QUICKSHIP

GP:50's program for fast, efficient delivery of Industrial Test and Control Products.
(Shipment in 2 days ARO)

Models 211 (0-5 Vdc), 311 (4-20 mA) and 311Z (4-20 mA, Intrinsically Safe) are available with all standard pressure ranges. Add any of the options below and you have a unit that will fit just about any application!

ORDERING:

Take a look below at our Easy To-Use Ordering Guide to select Model number, Accuracy, Pressure Range, Pressure Type and the Options that you need for your application, and expect shipment within 2 days ARO at no additional charge.



* Model 311Z only

MODEL	SERIES	RANGE	PRESSURE TYPE	OPTIONS
311	C	PT	2	CA/GJ

Example

MODEL

211 0-5 Vdc
311 4-20 mA
311Z 4-20 mA,
 Intrinsically Safe

ACCURACY

B 0.5% FSO
C 0.2% FSO

PRESSURE RANGE

PSI
PJ 5
PL 7.5
PN 10
PP 15
PQ 3-15
PR 20
PS 3-27
PO 25
PT 30
PV 50
PX 75
PZ 100
RB 150
RD 200
RE 250
RF 300
RH 500
RJ 600
RK 750
RM 1,000
RO 1,500
RR 2,000
RS 2,500
RT 3,000
RV 5,000
RX 7,500
RZ 10,000
SZ (0-5 TO 0-10,000)
 Non-Standard Range

PRESSURE TYPE

2 Gauge (0-299 psi)
4 Vacuum
7 Gauge (Non-Hermetic Seal / 300 psi & above)
8 Elevated
10 Compound (vacuum to gauge)

OPTIONS

AA No Options chosen (1/4" NPT (F) pressure port & HEYCO w/36" wire lead electrical connection)
CA Bendix 6-Pin connector (PTIH-10-6P), or equivalent (Mate: not inc.)
CF 1/2" NPT (M) thread with 36" potted leads
CH NEMA-4X Rating with 8' vented cable (299 psi & below)
CJ DIN 43650 (Hirshmann, w/mate) NEMA-4X (IP65)
CL 1/2" NPT (M) with 36" vented cable (299 psi & below)
CO Terminal block w/Junction box
GJ Add Zero & Span Controls (Approx. ±20% FSO Adjustment)
HK NEMA-4X Rating w/36" wire lead (300 psi & above)

GENERAL PURPOSE



QUICKSHIP

GP:50's program for fast, efficient delivery of **Melt Pressure Products**.
(Shipment in 5 days ARO)



PLASTIC MELT PRESSURE

ORDERING:

See the ordering guide below for the Models 31 and 35 series of Melt Pressure Transducers. Pick from the options below and receive a quick turnaround at **No additional Charge**, just the standard shipping charge.

MODELS 31 & 35:

Example

MODEL	RANGE	OPTIONS
331	RX	CF/GJ

MODEL

131 3.33 mV/V
231 0-5Vdc
331 4-20 mA

MODEL

135 3.33 mV/V
235 0-5Vdc
335 4-20 mA

PRESSURE RANGE

RV 5,000 psi
RX 7,500 psi
RZ 10,000 psi

CONNECTOR OPTIONS:

PTIH-10-6P Standard Connector
CC Bendix PC02E-12-8P
CD Cannon WK6-32S
CF 1/2" NPT (M) thread with 24" potted leads

OPTIONS

GJ Zero and Span controls (2xx and 3xx only)
GS 0-10Vdc Model 2XX only
ME Internal Calibration Resistor set to 80% ±0.5% FSO (for 300 series only)
GU Type K thermocouple (x35 only)

Wire termination to meet customer's requirements