



**MELT PRESSURE
TRANSDUCERS & TRANSMITTERS**
300 Industrial Drive, Grand Island, NY 14072 USA
Tel. (716)775-8830 • Fax (716)775-8020 • sales@gp50.com • www.gp50.com

Product Specification Sheet
MELT TEMPERATURE SENSORS
Models T30, T31

High quality Melt Temperature Sensors used to measure the process melt temperature of molten polymer.



FEATURES:

- All stainless Steel Construction
- Measures temperature up to 900°F (480°C)
- Includes thermocouple and mating connector

The standard unit offers a 6" rigid stem and 18" of flex capillary with either a 1/8" or flush sensing tip. All units offer the standard 1/2-20 UNF mounting thread.

ORDERING GUIDE

Use the following codes to identify desired item.

MODEL	TIP	SENSING	OPTIONS
•	+	•	+

MODEL

- T30** Rigid Stem Only
- T31** 6" Rigid Stem and 18" Flexible Tube

TIP

- F** Flush Tip
- T** 1/8" immersion depth

SENSING

- HQ** Thermocouple Type "J"
- GU** Thermocouple Type "K"
- JA** Platinum RTD

OPTIONS

- HD** 3" Rigid Stem
- GN** 12" Rigid Stem
- FB** M18 X 1.5 metric thread
- MT** Non-standard Armored Capillary tube (specify length)

GP:50 reserves the right to make product improvements and amendments to the product specifications stated throughout this brochure without prior notification. Please contact the factory on all critical dimensions and specifications for verification.